

C&C 27 Running Rigging Specs

Item	Material	Length	Remarks All materials dacron braid.
Main Halyard	3/8" bd	86'	Headboard Shackle
Main Boom Topping Lift	1/4" bd	75'	Heated & Whipped Both Ends
Main Cunningham	3/8" bd	3'	Lash Eye One End Heated & Whipped Other End
Main Sheet	7/16" bd	60'	Heated & Whipped Both Ends
Spinnaker Pole Topping Lift	3/8" bd	65'	Snap Shackle One End Heat & Whip Other End
Genoa Halyard	7/16" bd	86'	Heat & Whip One End Snap Shackle Other End
Genoa Sheets	7/16" bd	2x30'	Heated & Whipped Both Ends
Spinnaker Halyard	3/8" bd	88'	Whip Both Ends Tie On Snap Shackle
Spinnaker Sheets	3/8" bd	2x60'	Eye Splice With Snap Shackle and Shackle Guard
Spinnaker Pole Lift	3/8" bd	66'	Snap Shackle On One End Heat & Whip Other End
Spinnaker Pole Foreguy	3/8" bd	36'	Eye Splice with Snap Shackle Heat & Whip Other End
Reefing Lines (2)	3/8" bd	2x40'	Heated & Whip Both Ends
Main Clew Outhaul	3/8" bd	28'	Heat & Whip Both Ends
Adjustable Backstay Lanyard	3/8" bd	40'	Heat & Whip Both Ends
Midstay Lanyard	3/8" bd	25'	Heat & Whip Both Ends
Mainsheet Crosshaul	3/8" bd	17'	Heat & Whip Both Ends

C&C 27 Mark V Standing Rigging

Item	Size	Style	Upper Fitting	Lower Fitting	Remarks
Forestay	7/32"	1x19 s.s. Wire	- Stemball Eye & Toggle - Marine Eye	- Marine Eye	Jaw & Jaw Turnbuckle on Stem
Backstay	7/32"	1x19 s.s. Wire	- Stemball & Washer	- M.S. Eye	Adjusting Tackle Optional
Main Shroud	7/32"	1x19 s.s. Wire	- Stemball & Washer	- 7/32" Turnbuckle with Toggle	Stop Sleeve and Washer at Spreader Location
Lower Shroud	7/32"	1x19 s.s. Wire	- Stemball & Washer	- 7/32" (Turnbuckle with Toggle)	Stop Sleeve and Washer at Spreader Location
Midstay	3/16"	1x19 s.s. Wire	- Swaged Toggle with 3/8" Pin	- 3/16" Turnbuckle with Toggle	Block and Tackle Option
Adjustable Midstay	3/16"	1x19 s.s. Wire	- Swaged Toggle with 3/8" Pin	- 3/16" Fork	Block & Tackle Assembly with Shackle
Backstay Bridle	7/32"	1x19 s.s. Wire	- MS Fork	- Turnbuckle with Toggle	